

HUSAR WINCH BST 3000 LBS

BST 3000lbs	Technical specifications
Pull capacity(single line)	3000 lb (1361 kg)
Motor 12V	2.2kw / 2.9hp
Controls	Wired / wireless remote control
Gear ratio	153:1
Brake	Automatic
Rope	14m Ø 4,8mm
Fairlead	4- ways rollers fairlead
Net weight	10kg
Dimensions	(L x W x H) 324mm x113mm x108 mm



Line speed and motor current (first layer)						
Line pull	Lbs	0	500	1000	2000	3000
	Kgs	0	227	454	907	1361
Line speed	M/min	3,2	2,8	2,3	1,8	1,3
Motor current	Amps	18	30	90	130	180

Line pull and cable capacity						
Layer of cable		1	2	3	4	5
Rated line pull per layer	Lbs	3000	2370	1960	1670	1460
	Kgs	1361	1075	889	756	662
Cable capacity per layer	M	1,5	3,7	5,9	8,7	10

BST S 3000lbs	Technical specifications
Pull capacity(single line)	3000 lb / 1361 kr
Motor 12V	1.5 KM / 1,0 kw
Controls	Wired / wireless remote control
Gear ratio	138:1
Brake	Automatic
Rope	12m x Ø 4.8mm
Fairlead	4-ways rollers fairlead
Mounting bolt pattern	124mm x 76mm
Net weight	7,5kg
Dimensions	(L x W x H) 334 X 114 X 120mm

HUSAR WINCH BST S 3000 LBS



Line speed and motor current (first layer)					
Line pull	Lbs	0	1000	2000	3000
	Kgs	0	454	907	1360
Line speed	M/min	7,5	4,5	3,2	2,1
Motor current	Amps	15	75	120	175

Line pull and cable capacity					
Layer of cable		1	2	3	4
Rated line pull per layer	Lbs	3000	2520	2170	1870
	Kgs	1360	1140	985	849
Cable capacity per layer	M	2,2	4,8	7,9	12